

## Technical data: Angle profile Curve / Angle profile PRO Curve for straight and curved installation

Stand: 01.2025

Material		Strength	Tensile strength
W	Nirosta® stainless steel 1.4301 is a chrome-nickel steel (chrome content 18%, nickel content 8.5%)	1,5mm	1200 - 1300 N/mm <sup>2</sup>
Z	galvanised steel DX51D+z275MA-C	2,0mm	250 - 400 N/mm <sup>2</sup>
CT	terra-S antique steel, corten steel material S355J2WP	2,0mm	700 N/mm <sup>2</sup>
AL	Aluminium WG-B57S	2,0mm	200 N/mm <sup>2</sup>

Angle profile Curve		Angle profile PRO Curve
Angle (Height/Width)		Angle (Height/Width)
W	Angle 90/60 mm	-
Z	Angle 90/60 mm, 130/70, 210/75 mm	Angle 90/60 mm
CT	Angle 90/60 mm	Angle 90/60 mm
AL	Angle 90/60, 100/50 mm (Substrate rail)	-

Other angles possible on request.

	
<p>Angle profile Curve galvanised steel / Corten steel Angle 90/60 mm</p>	<p>PRO Curve angle profile with smooth visible side galvanised steel 90/60 mm angle</p>

### Visible width

The visible width of the rounded top edge is 10 mm, which serves as protection against injuries and prevents damage to the lawn mower.

### Flexible and mouldable

Angle profile Curve / Angle profile PRO Curve is 240 cm long and has 13 trapezoidal surfaces. The holes in the horizontal surfaces offer the option of additional fastening in the substructure, e.g. with pegs or concrete dowels. The recesses between the trapezoidal surfaces allow the angle profiles to be bent.